




FEATURES

Suspended extrusion with a deep profile and flat frosted lens that eliminates diode imaging with most LED tapelights. Preassembled 90° corners available, no miter cutting required. Versatile and ideal for general lighting, accents, displays, shelving, and signage.

SPECIFICATIONS

FINISH	Silver Anodized
LENS	Frosted
WATTAGE	1.5W/ft to 8.8W/ft
IP RATING	IP20 dry; IP65 wet; IP67 wet; IP68 wet
CCT / COLOR	2200K - 5200K; warm fade
BEAM SPREAD	114° typical
INPUT VOLTAGE	24VDC
LENGTH	Made to order. Actual lengths vary by LED tapelight cut points. Maximum assembled length is 94in. Lengths over 94in are made with multiple sections, shipped unassembled.
OUTPUT	66 to 367 lm/ft
LEDS	Single binned LEDs +/- 30-70 CCT, MacAdam 3 SDCM
MATERIAL	Extrusion - Anodized aluminum; Lens - Polycarbonate
MOUNTING	Suspension cables
POWER SUPPLY	Requires a 24V power supply
WARRANTY	IP20 - 5 year limited, IP65/67/68 - 3 year limited


DIMENSIONS






FACTORY ASSEMBLED CORNERS

No miter cuts required. Sold separately. Screws and joiners bars included.




90° INSIDE CORNER

LLI-XS-ELT-SF-90D-INS-8IN




90° OUTSIDE CORNER

LLI-XS-ELT-SF-90D-OUT-8IN




90° FLAT CORNER

LLI-XS-ELT-SF-90D-FLT-8IN




135° FLAT CORNER

LLI-XS-ELT-SF-135D-8IN



T CORNER

LLI-XS-ELT-SF-TEE-8IN



X CORNER

LLI-XS-ELT-SF-CROSS-8IN