

SPECIFIER			
PROJECT			
DATE			


# UNIVERSAL RF RECEIVER

## **UNIVERSAL - INDOOR**

#### LLI-C-RCV-UR-RF-4CH

CONTROLLER COMPATIBILITY	Compatible with all RF LLI-C-CTRL controllers.		
LED COMPATIBILITY	Static Color, Tunable White & RGB(W) LEDs		
CHANNELS	4 Channel, 8 Amp		
INPUT VOLTAGE	12V / 24V (power supply not included)		
CADACITY	12V - 96W		
CAPACITY	24V - 192W		
FEATURES	Can be controlled by up to (8) controllers Can be synchronized with unlimited receivers up to 320ft away		





#### **UNIVERSAL - WET**

### LLI-C-RCV-U-RF-4CH-WET

CONTROLLER COMPATIBILITY	Compatible with all RF LLI-C-CTRL controllers.		
IP RATING	IP66		
LED COMPATIBILITY	Static Color, Tunable White & RGB(W) LEDs		
CHANNELS	4 Channel, 8 Amp		
INPUT VOLTAGE	12V / 24V (power supply not included)		
CAPACITY	12V - 96W		
CAPACITY	24V - 192W		
OPERATING TEMP.	Maximum 167°F		
FEATURES	Can be controlled by up to (8) controllers Can be synchronized with (20) receivers		



