

DEEP GRAZER EXTRUSION + LED TAPELIGHT



5 YEAR
LIMITED
WARRANTY



SPECIFICATIONS

FINISH	Silver Anodized, Black Powder Coat, White Powder Coat
LENS	15° Grazing
WATTAGE	0.75W/ft to 7.6W/ft
IP RATING	IP20, IP65 - rating applies to tapelight, see page 2 for details
CCT / COLOR	2200K - 5200K; RGB; RGBW; tunable white; warm fade
BEAM SPREAD	15° typical with Grazing lens
INPUT VOLTAGE	24VDC
LENGTH	Made to order. Actual lengths vary by LED tapelight cut points. Maximum assembled length is 94in. Lengths over 94in are made with multiple sections, shipped unassembled.
OUTPUT	66 to 680 lm/ft
LEDS	Single binned LEDs +/- 30-70 CCT, MacAdam 3 SDCM
MATERIAL	Extrusion - Anodized aluminum; Lens - Polycarbonate
MOUNTING	Mounting clips recommended
POWER SUPPLY	Requires a 24V power supply - see page 5
WARRANTY	IP20 - 5 year limited, IP65 - 3 year limited

FEATURES & RECOMMENDED APPLICATIONS

Surface-mount extrusion with a deep profile and 15° Clear Grazing lens. Highlight textured walls and irregular surfaces, bringing features to life. Ideal for textured plaster, brick surfaces, stone facades, wave walls, and corrugated surfaces.



PRODUCT: LLI-DEP-SG-H4.4W-30K-24V-94IN

DEEP GRAZER EXTRUSION + LED TAPELIGHT

ORDERING GUIDE

← PRODUCT CODE

PROFILE LLI-DEP	1a. FINISH S	1b. LENS G	2. LED 2.2W	3. IP RATING* 65	4. CCT / COLOR 30K	5. LENGTH 48IN
---------------------------	------------------------	----------------------	-----------------------	----------------------------	------------------------------	--------------------------

Silver Black White
 Grazing
 WATTS/FT
 0.75-7.6 W/ft
 [blank] - IP20
 65 - IP65
 22K-52K
 Warm Fade
 Tunable White
 Static Color
 RGB
 RGBW

Enter overall length in inches. Length can be a complete section (if under max run) or separated into smaller sections. Nominal length only. Actual lengths vary by LED cut point.

OPTIONAL CODE →

6. MOUNTING [blank]	POWER FEED	
	7. LEAD TYPE [blank]	8. LEAD LENGTH [blank]
	9. FEED TYPE [blank]	

Default [blank] - Ships standard with standard clips.
 Refer to section 6 on the next page if you require alternate mounting.
 Default [blank] - 48" hard wire end feed (PWR48EF)
 Refer to section 7 on the next page for an alternate power feed configuration.

Example product code: **LLI-DEP-SG-4.4W-65-35K-24V-48IN**

More LED tapelight and color options available upon request. Visit www.llialighting.com or contact us for details.

1. FINISH & LENS

1a. FINISH	1b. LENS
S	G
S Silver Anodized finish	G 15° Clear Grazing lens
B Black Powder Coat finish	
W White Powder Coat finish	

2-4. LED TAPELIGHT OPTIONS

2. LED CODE H4.4W	3. IP RATING* [blank]	4. CCT / COLOR 30K
-----------------------------	---------------------------------	------------------------------

For IP20, leave [blank].

TECHNICAL DATA

	WATTAGE	DELIVERED LM/FT @ 30K*	CLEAR GRAZING LENS APPEARANCE**	CRI	MAX. RUN	CUT POINTS*
T0.75W (White)	0.75 W/ft	66 lm/ft	IMAGING	90+	26 ft	1"
1.5W (White)	1.5 W/ft	122 lm/ft	IMAGING	90+	60 ft*	3.9"
T1.5W (White)	1.5 W/ft	132 lm/ft	IMAGING	90+	26 ft	1"
2.2W (White)	2.2 W/ft	163 lm/ft	IMAGING	90+	60 ft*	3.9"
★ 2.5W (White)	2.5 W/ft	161 lm/ft	IMAGING	90+	32 ft	2"
T2.5W (White)	2.5 W/ft	174 lm/ft	IMAGING	90+	20 ft	1"
3.5W (White)	3.5 W/ft	205 lm/ft	IMAGING	90+	40 ft	2.5"
◆ WF3.5W (Warm Fade)	3.5 W/ft	231 lm/ft	IMAGING	90+	16 ft	2.5"
TW2.7W (Tunable White)	2.7 W/ft	239 lm/ft	IMAGING	90+	26 ft	3.3"
★ 4.4W (White)	4.4 W/ft	250 lm/ft	IMAGING	90+	32 ft	2"
H3.5W (White)	3.5 W/ft	310 lm/ft	IMAGING	90+	26 ft	2.5"
T5.0W (White)	5.0 W/ft	336 lm/ft	IMAGING	90+	13 ft	1"
★ H4.4W (White)	4.4 W/ft	400 lm/ft	IMAGING	90+	32 ft	2"
★ R5.4W (White, High R9)	5.4 W/ft	400 lm/ft	IMAGING	95+	16 ft	1"
TW5.3W (Tunable White)	5.3 W/ft	417 lm/ft	IMAGING	90+	16 ft	3.3"
H5.3W (White)	5.3 W/ft	581 lm/ft	IMAGING	90+	16 ft	2"
IC5.9W (White)	5.9 W/ft	618 lm/ft	IMAGING	90+	16ft	0.21"
★ HO5.9W (White)	5.9 W/ft	680 lm/ft	IMAGING	90+	16 ft	2"
C2.2W (Static Color)	2.2 W/ft	N/A	IMAGING	—	60 ft	3.9"
C4.4W (Static Color)	4.4 W/ft	N/A	IMAGING	—	32 ft	2"
CC4.4W (RGB)	4.4 W/ft	90 lm/ft	IMAGING	—	32 ft	3.9"
TC4.4W (RGB)	4.4 W/ft	131 lm/ft	IMAGING	—	16 ft	2"
★ CC5.9W (RGB)	5.9 W/ft	243 lm/ft	IMAGING	—	32 ft	2.8"
CW5.8W (RGBW)	5.8 W/ft	220 lm/ft	IMAGING	80+	32 ft	3.9"
CW7.0W (RGBW)	7.0 W/ft	255 lm/ft	IMAGING	90+	28 ft	2.5"
★ CW7.6W (RGBW)	7.6 W/ft	268 lm/ft	IMAGING	90+	16 ft	2.5"

* 1.5W and 2.2W IP65 tapelight maximum run is reduced to 50 ft, only IP20 may reach maximum run of 60 ft.

★ Recommended options.

◆ Warm Fade tapelight requires a UDEFF or 0-10V dimmable power supply.


** Diode visibility data tested at 100% output. Diodes may become more visible as tapelight dims.

* Lumen data based on frosted lens, IP20 tapelight, 30K white output, or combined output for tunable white, warm fade, RGB, and RGB(W) tapelights.

* Protection varies according to IP Rating. See below or refer to llialighting.com/resources for more information.

 IP20, uncoated - Dry Location

 IP65, silicone covered - Wet Location - Limited protection from water ingress. Not suitable for applications that may see pooling or standing water conditions. Not suitable for submersion.



DEEP GRAZER EXTRUSION + LED TAPELIGHT

ORDERING GUIDE (CONTINUED)

5. LENGTH

5.
LENGTH

48IN

Enter overall extrusion length in inches. Maximum assembled length is 94in. Lengths over 94in are made with multiple sections, shipped unassembled. Overall Extrusion+LED tapelight length will be rounded down based on nearest LED tapelight cut point.

6. MOUNTING (OPTIONAL)

6.
MOUNTING

[blank]

Default [blank] - Standard Clip


ADJ Adjustable Clip

STANDARD MOUNTING CLIP INCLUDED
UNLESS OTHERWISE SPECIFIED



0.70" W x 0.68" H x 0.56" L

ADJUSTABLE MOUNTING CLIP



0.67" W x 0.9" H x 0.67" L

7-9. POWER FEED (OPTIONAL)

7.
LEAD TYPE

8.
LEAD LENGTH

9.
FEED TYPE

[blank]

[blank]

[blank]





Default [blank] - 48" hard wire end feed (PWR48EF)

PWR Hard wire
MBC* Male barrel
FBC* Female barrel

Enter desired wire
length in inches.

EF End Feed
SL Left Side Feed
SR Right Side Feed
RF Rear Feed

STANDARD 48" HARD WIRE END FEED INCLUDED
UNLESS OTHERWISE SPECIFIED




Hard wire, no connector -
default (**PWR**)

Male barrel connector
(**MBC***)


Female barrel connector
(**FBC***)

*Barrel connectors not compatible with RGB, RGB(W),
or Tunable White tapelights.

WHAT'S INCLUDED




EXTRUSION WITH LENS



LED TAPELIGHT WITH
POWER FEED



ENDCAPS



MOUNTING CLIPS

DEEP GRAZER EXTRUSION + LED TAPELIGHT

LUMEN OUTPUT MULTIPLIERS (FOR ESTIMATING DELIVERED LUMENS)

COLOR TEMPERATURE	LUMEN MULTIPLIER
2200K	0.8
2700K	0.9
3000K	1
3500K	1.1
4200K	1.2
5200K	1.25

IP RATING	LUMEN MULTIPLIER
IP20	1
IP65	0.9



FINISH	LUMEN MULTIPLIER
Silver Anodized	1
Black Anodized	0.9
White Powder Coat	1.1

EXAMPLE: White Powder Coat Extrusion, 2.2W, IP65, 5200K

(Output @ 30K) x (Color temperature lumen multiplier) x (IP rating lumen multiplier) x (Finish lumen multiplier) = Estimated delivered lm/ft

156 lm/ft	x	1.25	x	0.9	x	1.1	=	193 lm/ft
-----------	---	------	---	-----	---	-----	---	-----------

PHOTOMETRY

LLI-DEP-SG-H4.4W-30K-24V*		BEAM SPREAD	POLAR CHART	CONICAL CHART
POWER (W/ft)	4.4W	15° 		ILLUMINANCE AT A DISTANCE 
OUTPUT (lm/ft)	382 lm/ft			
COLOR TEMPERATURE	3000K			
BEAM SPREAD	15°			
EFFICACY (lm/W)	87 lm/W			

*Information for other options available upon request. IES files for extrusion+tapelight available upon request.



POWER SUPPLIES SOLD SEPARATELY

DIMMABLE ELECTRONIC 0-10V

Optimal performance dims to 0%.*





PART NUMBER	CAPACITY	INPUT	OUTPUT	CLASS	LOCATION	L	W	H
LLI-PS-DE010-030W-24V-KO	30W	120V or 277V	24V	CLASS 2	IP66 WET	6.5"	3.6"	1.6"
LLI-PS-DE010-060W-24V-KO	60W	120V or 277V	24V	CLASS 2	IP66 WET	7.4"	3.6"	1.6"
LLI-PS-DE010-096W-24V-KO	96W	120V or 277V	24V	CLASS 2	IP66 WET	8.7"	3.7"	1.7"
LLI-PS-DE010-192W-24V-CL2-KO	2x96W	120V or 277V	24V	CLASS 2	IP66 WET	10.9"	4.3"	1.9"
LLI-PS-DE010-200W-24V-KO	200W	120V or 277V	24V	CLASS 1	IP66 WET	10.2"	4.1"	1.8"
LLI-PS-DE010-288W-24V-CL2-KO	3x96W	120V or 277V	24V	CLASS 2	IP66 WET	11.9"	4.3"	1.9"
LLI-PS-DE010-300W-24V-KO	300W	120V or 277V	24V	CLASS 1	IP66 WET	10.9"	4.3"	1.8"



NON-DIMMABLE ELECTRONIC



PART NUMBER	CAPACITY	INPUT	OUTPUT	CLASS	LOCATION	L	W	H
LLI-PS-NDE-030W-24V-KO	30W	100-277V	24V	CLASS 2	IP66 WET	6.5"	3.5"	1.02"
LLI-PS-NDE-060W-24V-KO	60W	100-277V	24V	CLASS 2	IP66 WET	7.4"	3.5"	1.2"
LLI-PS-NDE-096W-24V-KO	96W	100-277V	24V	CLASS 2	IP66 WET	8.7"	3.7"	1.7"
LLI-PS-NDE-192W-24V-CL2-KO	2x96W	100-277V	24V	CLASS 2	IP66 WET	10.9"	4.1"	1.9"
LLI-PS-NDE-200W-24V-KO	200W	100-277V	24V	CLASS 1	IP66 WET	10.3"	4.1"	1.8"
LLI-PS-NDE-288W-24V-CL2-KO	3x96W	100-277V	24V	CLASS 2	IP66 WET	11.9"	4.1"	1.9"
LLI-PS-NDE-300W-24V-KO	300W	100-277V	24V	CLASS 1	IP66 WET	10.9"	4.3"	1.8"





DIMMABLE ELECTRONIC FLICKER-FREE

Optimal performance dims to 2-5%.



PART NUMBER	CAPACITY	INPUT	OUTPUT	CLASS	LOCATION	L	W	H
LLI-PS-UDEFF-030W-24V-KO	30W	110-277V	24V	CLASS 2	IP66 WET	6.5"	3.6"	1.0"
LLI-PS-UDEFF-060W-24V-KO	60W	110-277V	24V	CLASS 2	IP66 WET	7.4"	3.6"	1.0"
LLI-PS-UDEFF-096W-24V-KO	96W	110-277V	24V	CLASS 2	IP66 WET	8.7"	3.7"	1.6"
LLI-PS-UDEFF-192W-24V-CL2-KO	2x96W	110-277V	24V	CLASS 2	IP66 WET	10.9"	4.3"	1.9"
LLI-PS-UDEFF-200W-24V-KO	200W	110-277V	24V	CLASS 1	IP66 WET	10.2"	4.1"	1.8"
LLI-PS-UDEFF-288W-24V-CL2-KO	3x96W	110-277V	24V	CLASS 2	IP66 WET	11.9"	4.3"	1.9"
LLI-PS-UDEFF-300W-24V-KO	300W	110-277V	24V	CLASS 1	IP66 WET	11.0"	4.3"	1.8"





DIMMABLE MAGNETIC

Optimal performance dims to 5-10%.*



PART NUMBER	CAPACITY	INPUT	OUTPUT	CLASS	LOCATION	L	W	H
LLI-PS-DM-020W-24V-KO	20W	120V or 277V	24V	CLASS 2	NEMA 3R WET	7.38"	2.11"	1.60"
LLI-PS-DM-040W-24V-KO	40W	120V or 277V	24V	CLASS 2	NEMA 3R WET	7.38"	2.11"	1.60"
LLI-PS-DM-060W-24V-KO	60W	120V or 277V	24V	CLASS 2	NEMA 3R WET	8.13"	3.93"	1.59"
LLI-PS-DM-100W-24V-KO	100W	120V or 277V	24V	CLASS 2	NEMA 3R WET	8.13"	3.93"	1.59"
LLI-PS-DM-150W-24V-KO	150W	120V or 277V	24V	CLASS 1	NEMA 3R WET	8.79"	4.15"	3.41"
LLI-PS-DM-200W-24V-KO	200W	120V or 277V	24V	CLASS 1	NEMA 3R WET	8.79"	4.15"	3.41"
LLI-PS-DM-300W-24V-KO	300W	120V or 277V	24V	CLASS 1	NEMA 3R WET	8.79"	4.15"	3.41"
LLI-PS-DM-300W-24V-CL2-KO	6 x 50W	120V or 277V	24V	CLASS 2	NEMA 3R WET	10.29"	5.69"	3.43"
LLI-PS-DM-600W-24V-KO	2 x 300W	120V or 277V	24V	CLASS 1	NEMA 3R WET	10.29"	6.79"	4.68"





LUTRON HI-LUME PREMIER 0.1% DIMMABLE ELECTRONIC

Soft-on, Fade-to-Black, continuous flicker-free dimming from 100% to 0.1.



PART NUMBER	CAPACITY	INPUT	OUTPUT	CLASS	LOCATION	L	W	H
L3D0-96W24V-U	96W	120-277V	24V	CLASS 2	IP20 DRY	10.5"	5.5"	2.0"



*Performance can be affected by driver loading and dimmer type.

CONTROLS (SOLD SEPARATELY)
