


LINE VOLTAGE 120VAC 2.5W LED TAPE - IP20



TECHNICAL INFORMATION

NOTE: All data has +/- 5% tolerance.

WATTAGE	2.5W per foot
IP RATING	IP20 - dry locations
OUTPUT	27K - 145 lm/ft 30K - 150 lm/ft 35K - 158 lm/ft 42K - 165 lm/ft 52K - 170 lm/ft
INPUT VOLTAGE	120VAC
OPERATING TEMP.	-4° to 104° F
CRI	90+
DIMMABLE	Yes, compatible with ELV reverse phase dimmers
SEGMENT LENGTH	Every 12", not field-cuttable
MAXIMUM RUN	164 feet
DIMENSIONS	Including endcaps: 1.16" W x 0.59" H Not including endcaps: 0.61" W x 0.4" H
ADHESIVE BACKING	None - Adhesive sold separately by 100ft reel
LIFESPAN	50,000 hrs
WARRANTY	3 year limited
POWER SUPPLY	Not required

CONNECTOR OPTIONS (SOLD SEPARATELY)

This product is not field-cuttable. All custom connections must be factory assembled. See page 2 for available connector options.

MOUNTING OPTIONS (SOLD SEPARATELY)



Tape Mounting Clip

LLI-LAC-MCL

0.43" L x 0.58" H x 0.78" W

Recommended use: 1 clip for every 12in.



120V Extrusions
(see page 2 for details)


ORDERING GUIDE

Example part number: LLI-LAC2.5W-20-27K-120V-90-164in

SERIES	IP RATING	COLOR	VOLTAGE	CRI	LENGTH
LLI-LAC2.5W	20		120V	90	
		27K (145 lm/ft)			(enter length in inches, up to 1,968")
		30K (150 lm/ft)			
		35K (158 lm/ft)			
		42K (165 lm/ft)			
		52K (170 lm/ft)			

LINE VOLTAGE 120VAC 2.5W LED TAPE - IP20

POWER FEED & CONNECTOR OPTIONS (IP20)




POWER FEED WITH 2-PRONG PLUG, 48IN
(replaceable 5A fuse included in plug end)

LLI-LAC-20-PWR-P-48IN



HARDWIRE POWER FEED
(single use 5A fuse included)

LLI-LAC-20-PWR-HW - 48IN
120IN



POWER FEED WITH 2-PRONG PLUG, 48IN
(with connector for extending power feed runs, replaceable 5A fuse located in plug end)

LLI-LAC-20-PWR-PC-48IN




POWER FEED EXTENSION CABLE, 24IN
(compatible with LLI-LAC-20-PWR-PC-48IN only)

LLI-LAC-20-PWR-EXT-24IN



TAPE TO TAPE CONNECTOR, 6IN

LLI-LAC-20-COR-6IN



TAPE TO TAPE CONNECTOR, 24IN

LLI-LAC-20-COR-24IN


MOUNTING EXTRUSION OPTIONS (SOLD SEPARATELY)



MOUNTING EXTRUSION - FLAT LENS

LLI-LAC-EXT-SQR-SA-F-94IN

- 94" L x 0.79" H x 0.79" W
- Features: Frosted lens
- Silver Anodized finish
- 2 endcaps
- 4 mounting clips



ADJUSTABLE MOUNTING CLIP



LLI-LAC-EXT-BKT-ADJ

For use with extrusions only.



MOUNTING EXTRUSION - TALL LENS

LLI-LAC-EXT-RCT-SA-F-94IN

- 94" L x 1.18" H x 0.79" W
- Features: Frosted lens
- Silver Anodized finish
- 2 endcaps
- 4 mounting clips






IMAGE COMING SOON

MOUNTING EXTRUSION - NO LENS

LLI-LAC-EXT-SA-94IN

- 94" L x 0.25" H x 0.79" W
- Features: Silver Anodized finish
- 4 mounting clips



LINE VOLTAGE 120VAC 2.5W LED TAPE - IP20

OVERALL LENGTH / CUT POINT GUIDE

Measurements listed below include end cap and power connection lengths.

13 1/2"	25 1/2"	37 1/2"	49 1/2"	61 1/2"	73 1/2"	85 1/2"	97 1/2"	109 1/2"	121 1/2"	133 1/2"	145 1/2"
157 1/2"	169 1/2"	181 1/2"	193 1/2"	205 1/2"	217 1/2"	229 1/2"	241 1/2"	253 1/2"	265 1/2"	277 1/2"	289 1/2"
301 1/2"	313 1/2"	325 1/2"	337 1/2"	349 1/2"	361 1/2"	373 1/2"	385 1/2"	397 1/2"	409 1/2"	421 1/2"	433 1/2"
445 1/2"	457 1/2"	469 1/2"	481 1/2"	493 1/2"	505 1/2"	517 1/2"	529 1/2"	541 1/2"	553 1/2"	565 1/2"	577 1/2"
589 1/2"	601 1/2"	613 1/2"	625 1/2"	637 1/2"	649 1/2"	661 1/2"	673 1/2"	685 1/2"	697 1/2"	709 1/2"	721 1/2"
733 1/2"	745 1/2"	757 1/2"	769 1/2"	781 1/2"	793 1/2"	805 1/2"	817 1/2"	829 1/2"	841 1/2"	853 1/2"	865 1/2"
877 1/2"	889 1/2"	901 1/2"	913 1/2"	925 1/2"	937 1/2"	949 1/2"	961 1/2"	973 1/2"	985 1/2"	997 1/2"	1,009 1/2"
1,021 1/2"	1,033 1/2"	1,045 1/2"	1,057 1/2"	1,069 1/2"	1,081 1/2"	1,093 1/2"	1,105 1/2"	1,117 1/2"	1,129 1/2"	1,141 1/2"	1,153 1/2"
1,165 1/2"	1,177 1/2"	1,189 1/2"	1,201 1/2"	1,213 1/2"	1,225 1/2"	1,237 1/2"	1,249 1/2"	1,261 1/2"	1,273 1/2"	1,285 1/2"	1,297 1/2"
1,309 1/2"	1,321 1/2"	1,333 1/2"	1,345 1/2"	1,357 1/2"	1,369 1/2"	1,381 1/2"	1,393 1/2"	1,405 1/2"	1,417 1/2"	1,429 1/2"	1,441 1/2"
1,453 1/2"	1,465 1/2"	1,477 1/2"	1,489 1/2"	1,501 1/2"	1,513 1/2"	1,525 1/2"	1,537 1/2"	1,549 1/2"	1,561 1/2"	1,573 1/2"	1,585 1/2"
1,597 1/2"	1,609 1/2"	1,621 1/2"	1,633 1/2"	1,645 1/2"	1,657 1/2"	1,669 1/2"	1,681 1/2"	1,693 1/2"	1,705 1/2"	1,717 1/2"	1,729 1/2"
1,741 1/2"	1,753 1/2"	1,765 1/2"	1,777 1/2"	1,789 1/2"	1,801 1/2"	1,813 1/2"	1,825 1/2"	1,837 1/2"	1,849 1/2"	1,861 1/2"	1,873 1/2"
1,885 1/2"	1,897 1/2"	1,909 1/2"	1,921 1/2"	1,933 1/2"	1,945 1/2"	1,957 1/2"	1,969 1/2"				