


LINE VOLTAGE 120VAC 4.0W LED TAPE - IP20



TECHNICAL INFORMATION


NOTE: All data has +/- 5% tolerance.

WATTAGE	4.0W per foot
IP RATING	IP20 - dry locations
OUTPUT	2700K - 350 lm/ft 3000K - 360 lm/ft 3500K - 370 lm/ft 4200K - 380 lm/ft 5200K - 390 lm/ft
INPUT VOLTAGE	120VAC
OPERATING TEMP.	-4° to 104° F
CRI	80+
DIMMABLE	Yes, compatible with ELV reverse phase dimmers
SEGMENT LENGTH	Every 4", not field-cuttable
MAXIMUM RUN	164 feet
DIMENSIONS	Including endcaps: 1.16" W x 0.59" H Not including endcaps: 0.61" W x 0.23" H
ADHESIVE BACKING	None - Adhesive sold separately by 100ft reel
LIFESPAN	50,000 hrs
WARRANTY	3 year limited
POWER SUPPLY	Not required

CONNECTOR OPTIONS (SOLD SEPARATELY)

This product is not field-cuttable. All custom connections must be factory assembled. See page 2 for available connector options.

MOUNTING OPTIONS (SOLD SEPARATELY)




Tape Mounting Clip

LLI-LAC-MCL

0.43" L x 0.58" H x 0.78" W

Recommended use: 1 clip for every 12in.



120V Extrusions
(see page 2 for details)

PART NUMBER BUILDER / ORDERING GUIDE


Example part number: LLI-LAC4.0W-20-27K-120V-80-164in

If a custom, pre-assembled layout is desired, please use the layout guide on page 3 to specify a layout code

SERIES	IP RATING	COLOR	VOLTAGE	CRI	LENGTH
LLI-LAC4.0W	20		120V	80	
		27K (350 lm/ft)			(enter length in inches, up to 1,968")
		30K (360 lm/ft)			
		35K (370 lm/ft)			
		42K (380 lm/ft)			
		52K (390 lm/ft)			

LINE VOLTAGE 120VAC 4.0W LED TAPE - IP20

POWER FEED & CONNECTION OPTIONS (IP20)



POWER FEED WITH 2-PRONG PLUG, 48IN
(replaceable 5A fuse included in plug end)


LLI-LAC-20-PWR-P-48IN



HARDWIRE POWER FEED
(single use 5A fuse included)

LLI-LAC-20-PWR-HW -

48IN
120IN



POWER FEED WITH 2-PRONG PLUG, 48IN
(with connector for extending power feed runs, replaceable 5A fuse located in plug end)

LLI-LAC-20-PWR-PC-48IN




POWER FEED EXTENSION CABLE, 24IN
(compatible with LLI-LAC-20-PWR-PC-48IN only)

LLI-LAC-20-PWR-EXT-24IN



TAPE TO TAPE CONNECTOR, 6IN


LLI-LAC-20-COR-6IN



TAPE TO TAPE CONNECTOR, 24IN

LLI-LAC-20-COR-24IN



MOUNTING EXTRUSION OPTIONS (SOLD SEPARATELY)



MOUNTING EXTRUSION - FLAT LENS

LLI-LAC-EXT-SQR-SA-F-94IN



94" L x 0.79" H x 0.79" W
Features: Frosted lens
Silver Anodized finish
2 endcaps
4 mounting clips



MOUNTING EXTRUSION - TALL LENS

LLI-LAC-EXT-RCT-SA-F-94IN


94" L x 1.18" H x 0.79" W
Features: Frosted lens
Silver Anodized finish
2 endcaps
4 mounting clips



MOUNTING EXTRUSION - NO LENS

LLI-LAC-EXT-SA-94IN

94" L x 0.25" H x 0.79" W
Features: Silver Anodized finish
4 mounting clips



ADJUSTABLE MOUNTING CLIP



LLI-LAC-EXT-BKT-ADJ

2.17" L x 1.81" H x 1.35" W
For use with extrusions only.

LINE VOLTAGE 120VAC 4.0W LED TAPE - IP20

OVERALL LENGTH / CUT POINT GUIDE

Measurements listed below include end cap and power connection lengths.

5 1/2"	9 1/2"	13 1/2"	17 1/2"	21 1/2"	25 1/2"	29 1/2"	33 1/2"	37 1/2"	41 1/2"	45 1/2"	49 1/2"
53 1/2"	57 1/2"	61 1/2"	65 1/2"	69 1/2"	73 1/2"	77 1/2"	81 1/2"	85 1/2"	89 1/2"	93 1/2"	97 1/2"
101 1/2"	105 1/2"	109 1/2"	113 1/2"	117 1/2"	121 1/2"	125 1/2"	129 1/2"	133 1/2"	137 1/2"	141 1/2"	145 1/2"
149 1/2"	153 1/2"	157 1/2"	161 1/2"	165 1/2"	169 1/2"	173 1/2"	177 1/2"	181 1/2"	185 1/2"	189 1/2"	193 1/2"
197 1/2"	201 1/2"	205 1/2"	209 1/2"	213 1/2"	217 1/2"	221 1/2"	225 1/2"	229 1/2"	233 1/2"	237 1/2"	241 1/2"
245 1/2"	249 1/2"	253 1/2"	257 1/2"	261 1/2"	265 1/2"	269 1/2"	273 1/2"	277 1/2"	281 1/2"	285 1/2"	289 1/2"
293 1/2"	297 1/2"	301 1/2"	305 1/2"	309 1/2"	313 1/2"	317 1/2"	321 1/2"	325 1/2"	329 1/2"	333 1/2"	337 1/2"
341 1/2"	345 1/2"	349 1/2"	353 1/2"	357 1/2"	361 1/2"	365 1/2"	369 1/2"	373 1/2"	377 1/2"	381 1/2"	385 1/2"
389 1/2"	393 1/2"	397 1/2"	401 1/2"	405 1/2"	409 1/2"	413 1/2"	417 1/2"	421 1/2"	425 1/2"	429 1/2"	433 1/2"
437 1/2"	441 1/2"	445 1/2"	449 1/2"	453 1/2"	457 1/2"	461 1/2"	465 1/2"	469 1/2"	473 1/2"	477 1/2"	481 1/2"
485 1/2"	489 1/2"	493 1/2"	497 1/2"	501 1/2"	505 1/2"	509 1/2"	513 1/2"	517 1/2"	521 1/2"	525 1/2"	529 1/2"
533 1/2"	537 1/2"	541 1/2"	545 1/2"	549 1/2"	553 1/2"	557 1/2"	561 1/2"	565 1/2"	569 1/2"	573 1/2"	577 1/2"
581 1/2"	585 1/2"	589 1/2"	593 1/2"	597 1/2"	601 1/2"	605 1/2"	609 1/2"	613 1/2"	617 1/2"	621 1/2"	625 1/2"
629 1/2"	633 1/2"	637 1/2"	641 1/2"	645 1/2"	649 1/2"	653 1/2"	657 1/2"	661 1/2"	665 1/2"	669 1/2"	673 1/2"
677 1/2"	681 1/2"	685 1/2"	689 1/2"	693 1/2"	697 1/2"	701 1/2"	705 1/2"	709 1/2"	713 1/2"	717 1/2"	721 1/2"
725 1/2"	729 1/2"	733 1/2"	737 1/2"	741 1/2"	745 1/2"	749 1/2"	753 1/2"	757 1/2"	761 1/2"	765 1/2"	769 1/2"
773 1/2"	777 1/2"	781 1/2"	785 1/2"	789 1/2"	793 1/2"	797 1/2"	801 1/2"	805 1/2"	809 1/2"	813 1/2"	817 1/2"
821 1/2"	825 1/2"	829 1/2"	833 1/2"	837 1/2"	841 1/2"	845 1/2"	849 1/2"	853 1/2"	857 1/2"	861 1/2"	865 1/2"
869 1/2"	873 1/2"	877 1/2"	881 1/2"	885 1/2"	889 1/2"	893 1/2"	897 1/2"	901 1/2"	905 1/2"	909 1/2"	913 1/2"
917 1/2"	921 1/2"	925 1/2"	929 1/2"	933 1/2"	937 1/2"	941 1/2"	945 1/2"	949 1/2"	953 1/2"	957 1/2"	961 1/2"
965 1/2"	969 1/2"	973 1/2"	977 1/2"	981 1/2"	985 1/2"	989 1/2"	993 1/2"	997 1/2"	1,001 1/2"	1,005 1/2"	1,009 1/2"
1,013 1/2"	1,017 1/2"	1,021 1/2"	1,025 1/2"	1,029 1/2"	1,033 1/2"	1,037 1/2"	1,041 1/2"	1,045 1/2"	1,049 1/2"	1,053 1/2"	1,057 1/2"
1,061 1/2"	1,065 1/2"	1,069 1/2"	1,073 1/2"	1,077 1/2"	1,081 1/2"	1,085 1/2"	1,089 1/2"	1,093 1/2"	1,097 1/2"	1,101 1/2"	1,105 1/2"
1,109 1/2"	1,113 1/2"	1,117 1/2"	1,121 1/2"	1,125 1/2"	1,129 1/2"	1,133 1/2"	1,137 1/2"	1,141 1/2"	1,145 1/2"	1,149 1/2"	1,153 1/2"
1,157 1/2"	1,161 1/2"	1,165 1/2"	1,169 1/2"	1,173 1/2"	1,177 1/2"	1,181 1/2"	1,185 1/2"	1,189 1/2"	1,193 1/2"	1,197 1/2"	1,201 1/2"
1,205 1/2"	1,209 1/2"	1,213 1/2"	1,217 1/2"	1,221 1/2"	1,225 1/2"	1,229 1/2"	1,233 1/2"	1,237 1/2"	1,241 1/2"	1,245 1/2"	1,249 1/2"
1,253 1/2"	1,257 1/2"	1,261 1/2"	1,265 1/2"	1,269 1/2"	1,273 1/2"	1,277 1/2"	1,281 1/2"	1,285 1/2"	1,289 1/2"	1,293 1/2"	1,297 1/2"
1,301 1/2"	1,305 1/2"	1,309 1/2"	1,313 1/2"	1,317 1/2"	1,321 1/2"	1,325 1/2"	1,329 1/2"	1,333 1/2"	1,337 1/2"	1,341 1/2"	1,345 1/2"
1,349 1/2"	1,353 1/2"	1,357 1/2"	1,361 1/2"	1,365 1/2"	1,369 1/2"	1,373 1/2"	1,377 1/2"	1,381 1/2"	1,385 1/2"	1,389 1/2"	1,393 1/2"
1,397 1/2"	1,401 1/2"	1,405 1/2"	1,409 1/2"	1,413 1/2"	1,417 1/2"	1,421 1/2"	1,425 1/2"	1,429 1/2"	1,433 1/2"	1,437 1/2"	1,441 1/2"
1,445 1/2"	1,449 1/2"	1,453 1/2"	1,457 1/2"	1,461 1/2"	1,465 1/2"	1,469 1/2"	1,473 1/2"	1,477 1/2"	1,481 1/2"	1,485 1/2"	1,489 1/2"
1,493 1/2"	1,497 1/2"	1,501 1/2"	1,505 1/2"	1,509 1/2"	1,513 1/2"	1,517 1/2"	1,521 1/2"	1,525 1/2"	1,529 1/2"	1,533 1/2"	1,537 1/2"
1,541 1/2"	1,545 1/2"	1,549 1/2"	1,553 1/2"	1,557 1/2"	1,561 1/2"	1,565 1/2"	1,569 1/2"	1,573 1/2"	1,577 1/2"	1,581 1/2"	1,585 1/2"
1,589 1/2"	1,593 1/2"	1,597 1/2"	1,601 1/2"	1,605 1/2"	1,609 1/2"	1,613 1/2"	1,617 1/2"	1,621 1/2"	1,625 1/2"	1,629 1/2"	1,633 1/2"
1,637 1/2"	1,641 1/2"	1,645 1/2"	1,649 1/2"	1,653 1/2"	1,657 1/2"	1,661 1/2"	1,665 1/2"	1,669 1/2"	1,673 1/2"	1,677 1/2"	1,681 1/2"
1,685 1/2"	1,689 1/2"	1,693 1/2"	1,697 1/2"	1,701 1/2"	1,705 1/2"	1,709 1/2"	1,713 1/2"	1,717 1/2"	1,721 1/2"	1,725 1/2"	1,729 1/2"
1,733 1/2"	1,737 1/2"	1,741 1/2"	1,745 1/2"	1,749 1/2"	1,753 1/2"	1,757 1/2"	1,761 1/2"	1,765 1/2"	1,769 1/2"	1,773 1/2"	1,777 1/2"
1,781 1/2"	1,785 1/2"	1,789 1/2"	1,793 1/2"	1,797 1/2"	1,801 1/2"	1,805 1/2"	1,809 1/2"	1,813 1/2"	1,817 1/2"	1,821 1/2"	1,825 1/2"
1,829 1/2"	1,833 1/2"	1,837 1/2"	1,841 1/2"	1,845 1/2"	1,849 1/2"	1,853 1/2"	1,857 1/2"	1,861 1/2"	1,865 1/2"	1,869 1/2"	1,873 1/2"
1,877 1/2"	1,881 1/2"	1,885 1/2"	1,889 1/2"	1,893 1/2"	1,897 1/2"	1,901 1/2"	1,905 1/2"	1,909 1/2"	1,913 1/2"	1,917 1/2"	1,921 1/2"
1,925 1/2"	1,929 1/2"	1,933 1/2"	1,937 1/2"	1,941 1/2"	1,945 1/2"	1,949 1/2"	1,953 1/2"	1,957 1/2"	1,961 1/2"	1,965 1/2"	1,969 1/2"