


# TIGHT PITCH 0.75W LED TAPELIGHT - IP20




## TECHNICAL INFORMATION


NOTE: All data has +/- 5% tolerance.

WATTAGE	0.75W per foot
IP RATING	IP20 - dry locations
OUTPUT	2200K - 79 lm/ft 2700K - 83 lm/ft 3000K - 87 lm/ft 3500K - 92 lm/ft 4200K - 96 lm/ft 5200K - 101 lm/ft
INPUT VOLTAGE	24VDC
OPERATING TEMP.	-13° to 140 °F
CRI	90+
CUT LENGTH	Every 1", or every 7 LEDs
MAXIMUM RUN	26 feet
DIMENSIONS	0.4" W x 0.08" H (10mm x 2.0mm)
ADHESIVE BACKING	Yes - VHB
LIFESPAN	50,000 hrs
WARRANTY	5 year limited
POWER SUPPLY	Compatible with all 24VDC power supplies -- see page 3

### LEAD TYPES



### MOUNTING



### EXTRUSIONS




## ORDERING GUIDE

← PRODUCT CODE						OPTIONAL CODE →	
SERIES	IP RATING	COLOR	VOLTAGE	CRI	LENGTH	POWER FEED	
LLI-LTP0.75W	20		24V	90		LEAD TYPE	LEAD LENGTH
		22K (79 lm/ft)			(enter length in inches, up to 312")		
		27K (83 lm/ft)					
		30K (87 lm/ft)					
		35K (92 lm/ft)					
		42K (96 lm/ft)					
		52K (101 lm/ft)					
Example part number: LLI-LTP0.75W-20-35K-24V-90-96in Default 48in power wire (PWR48) included on all custom lengths. Use OPTIONAL section to specify other power feed(s).						Default [blank] - 48" hard wire end feed (PWR48)  PWR Hard wire (no connector) Enter desired wire length in inches MBC Male barrel connector FBC Female barrel connector N/A ^ No lead attached  ^Compatible with DIY connectors, see page 2	


# TIGHT PITCH 0.75W LED TAPELIGHT - IP20

## DIY CONNECTORS (OPTIONAL)


Solderless connectors for quick in-field connection. DIY connectors are not compatible with all mounting extrusions. Reference [compatibility chart](#) for product compatibility.




TAPE-TO-TAPE  
BLOCK CONNECTOR,  
BLACK  
LLI-BC-LL-SC



TAPE-TO-WIRE  
BLOCK CONNECTOR,  
BLACK  
LLI-BC-LW-SC



TAPE-TO-TAPE  
GRIPPER CONNECTOR,  
BLACK/CLEAR  
LLI-GC-LL-SC



TAPE-TO-WIRE  
GRIPPER CONNECTOR,  
BLACK/CLEAR  
LLI-GC-LW-SC

## OVERALL LENGTH / CUT POINT GUIDE

1.0"	2.0"	3.0"	3.9"	4.9"	5.9"	6.9"	7.9"	8.9"	9.8"	10.8"	11.8"
12.8"	13.8"	14.8"	15.7"	16.7"	17.7"	18.7"	19.7"	20.7"	21.7"	22.6"	23.6"
24.6"	25.6"	26.6"	27.6"	28.5"	29.5"	30.5"	31.5"	32.5"	33.5"	34.4"	35.4"
36.4"	37.4"	38.4"	39.4"	40.4"	41.3"	42.3"	43.3"	44.3"	45.3"	46.3"	47.2"
48.2"	49.2"	50.2"	51.2"	52.2"	53.1"	54.1"	55.1"	56.1"	57.1"	58.1"	59.1"
60.0"	61.0"	62.0"	63.0"	64.0"	65.0"	65.9"	66.9"	67.9"	68.9"	69.9"	70.9"
71.9"	72.8"	73.8"	74.8"	75.8"	76.8"	77.8"	78.7"	79.7"	80.7"	81.7"	82.7"
83.7"	84.6"	85.6"	86.6"	87.6"	88.6"	89.6"	90.6"	91.5"	92.5"	93.5"	94.5"
95.5"	96.5"	97.4"	98.4"	99.4"	100.4"	101.4"	102.4"	103.3"	104.3"	105.3"	106.3"
107.3"	108.3"	109.3"	110.2"	111.2"	112.2"	113.2"	114.2"	115.2"	116.1"	117.1"	118.1"
119.1"	120.1"	121.1"	122.0"	123.0"	124.0"	125.0"	126.0"	127.0"	128.0"	128.9"	129.9"
130.9"	131.9"	132.9"	133.9"	134.8"	135.8"	136.8"	137.8"	138.8"	139.8"	140.7"	141.7"
142.7"	143.7"	144.7"	145.7"	146.7"	147.6"	148.6"	149.6"	150.6"	151.6"	152.6"	153.5"
154.5"	155.5"	156.5"	157.5"	158.5"	159.4"	160.4"	161.4"	162.4"	163.4"	164.4"	165.4"
166.3"	167.3"	168.3"	169.3"	170.3"	171.3"	172.2"	173.2"	174.2"	175.2"	176.2"	177.2"
178.1"	179.1"	180.1"	181.1"	182.1"	183.1"	184.1"	185.0"	186.0"	187.0"	188.0"	189.0"
190.0"	190.9"	191.9"	192.9"	193.9"	194.9"	195.9"	196.9"	197.8"	198.8"	199.8"	200.8"
201.8"	202.8"	203.7"	204.7"	205.7"	206.7"	207.7"	208.7"	209.6"	210.6"	211.6"	212.6"
213.6"	214.6"	215.6"	216.5"	217.5"	218.5"	219.5"	220.5"	221.5"	222.4"	223.4"	224.4"
225.4"	226.4"	227.4"	228.3"	229.3"	230.3"	231.3"	232.3"	233.3"	234.3"	235.2"	236.2"
237.2"	238.2"	239.2"	240.2"	241.1"	242.1"	243.1"	244.1"	245.1"	246.1"	247.0"	248.0"
249.0"	250.0"	251.0"	252.0"	253.0"	253.9"	254.9"	255.9"	256.9"	257.9"	258.9"	259.8"
260.8"	261.8"	262.8"	263.8"	264.8"	265.7"	266.7"	267.7"	268.7"	269.7"	270.7"	271.7"
272.6"	273.6"	274.6"	275.6"	276.6"	277.6"	278.5"	279.5"	280.5"	281.5"	282.5"	283.5"
284.4"	285.4"	286.4"	287.4"	288.4"	289.4"	290.4"	291.3"	292.3"	293.3"	294.3"	295.3"
296.3"	297.2"	298.2"	299.2"	300.2"	301.2"	302.2"	303.1"	304.1"	305.1"	306.1"	307.1"
308.1"	309.1"	310.0"	311.0"	312.0"							


**POWER SUPPLIES** SOLD SEPARATELY

**DIMMABLE ELECTRONIC 0-10V**



Optimal performance dims to 0%.\*


PART NUMBER	CAPACITY	INPUT	OUTPUT	CLASS	LOCATION	L	W	H
LLI-PS-DE010-030W-24V-KO	30W	120V or 277V	24V	CLASS 2	IP66 WET	6.5"	3.6"	1.6"
LLI-PS-DE010-060W-24V-KO	60W	120V or 277V	24V	CLASS 2	IP66 WET	7.4"	3.6"	1.6"
LLI-PS-DE010-096W-24V-KO	96W	120V or 277V	24V	CLASS 2	IP66 WET	8.7"	3.7"	1.7"
LLI-PS-DE010-192W-24V-CL2-KO	2x96W	120V or 277V	24V	CLASS 2	IP66 WET	10.9"	4.3"	1.9"
LLI-PS-DE010-200W-24V-KO	200W	120V or 277V	24V	CLASS 1	IP66 WET	10.2"	4.1"	1.8"
LLI-PS-DE010-288W-24V-CL2-KO	3x96W	120V or 277V	24V	CLASS 2	IP66 WET	11.9"	4.3"	1.9"
LLI-PS-DE010-300W-24V-KO	300W	120V or 277V	24V	CLASS 1	IP66 WET	10.9"	4.3"	1.8"



**NON-DIMMABLE ELECTRONIC**



PART NUMBER	CAPACITY	INPUT	OUTPUT	CLASS	LOCATION	L	W	H
LLI-PS-NDE-030W-24V-KO	30W	100-277V	24V	CLASS 2	IP66 WET	6.5"	3.5"	1.02"
LLI-PS-NDE-060W-24V-KO	60W	100-277V	24V	CLASS 2	IP66 WET	7.4"	3.5"	1.2"
LLI-PS-NDE-096W-24V-KO	96W	100-277V	24V	CLASS 2	IP66 WET	8.7"	3.7"	1.7"
LLI-PS-NDE-192W-24V-CL2-KO	2x96W	100-277V	24V	CLASS 2	IP66 WET	10.9"	4.1"	1.9"
LLI-PS-NDE-200W-24V-KO	200W	100-277V	24V	CLASS 1	IP66 WET	10.3"	4.1"	1.8"
LLI-PS-NDE-288W-24V-CL2-KO	3x96W	100-277V	24V	CLASS 2	IP66 WET	11.9"	4.1"	1.9"
LLI-PS-NDE-300W-24V-KO	300W	100-277V	24V	CLASS 1	IP66 WET	10.9"	4.3"	1.8"




**DIMMABLE ELECTRONIC FLICKER-FREE**



Optimal performance dims to 2-5%.

PART NUMBER	CAPACITY	INPUT	OUTPUT	CLASS	LOCATION	L	W	H
LLI-PS-UDEFF-030W-24V-KO	30W	110-277V	24V	CLASS 2	IP66 WET	6.5"	3.6"	1.0"
LLI-PS-UDEFF-060W-24V-KO	60W	110-277V	24V	CLASS 2	IP66 WET	7.4"	3.6"	1.0"
LLI-PS-UDEFF-096W-24V-KO	96W	110-277V	24V	CLASS 2	IP66 WET	8.7"	3.7"	1.6"
LLI-PS-UDEFF-192W-24V-CL2-KO	2x96W	110-277V	24V	CLASS 2	IP66 WET	10.9"	4.3"	1.9"
LLI-PS-UDEFF-200W-24V-KO	200W	110-277V	24V	CLASS 1	IP66 WET	10.2"	4.1"	1.8"
LLI-PS-UDEFF-288W-24V-CL2-KO	3x96W	110-277V	24V	CLASS 2	IP66 WET	11.9"	4.3"	1.9"
LLI-PS-UDEFF-300W-24V-KO	300W	110-277V	24V	CLASS 1	IP66 WET	11.0"	4.3"	1.8"




**DIMMABLE MAGNETIC**



Optimal performance dims to 5-10%.\*

PART NUMBER	CAPACITY	INPUT	OUTPUT	CLASS	LOCATION	L	W	H
LLI-PS-DM-020W-24V-KO	20W	120V or 277V	24V	CLASS 2	NEMA 3R WET	7.38"	2.11"	1.60"
LLI-PS-DM-040W-24V-KO	40W	120V or 277V	24V	CLASS 2	NEMA 3R WET	7.38"	2.11"	1.60"
LLI-PS-DM-060W-24V-KO	60W	120V or 277V	24V	CLASS 2	NEMA 3R WET	8.13"	3.93"	1.59"
LLI-PS-DM-100W-24V-KO	100W	120V or 277V	24V	CLASS 2	NEMA 3R WET	8.13"	3.93"	1.59"
LLI-PS-DM-150W-24V-KO	150W	120V or 277V	24V	CLASS 1	NEMA 3R WET	8.79"	4.15"	3.41"
LLI-PS-DM-200W-24V-KO	200W	120V or 277V	24V	CLASS 1	NEMA 3R WET	8.79"	4.15"	3.41"
LLI-PS-DM-300W-24V-KO	300W	120V or 277V	24V	CLASS 1	NEMA 3R WET	8.79"	4.15"	3.41"
LLI-PS-DM-300W-24V-CL2-KO	6 x 50W	120V or 277V	24V	CLASS 2	NEMA 3R WET	10.29"	5.69"	3.43"
LLI-PS-DM-600W-24V-KO	2 x 300W	120V or 277V	24V	CLASS 1	NEMA 3R WET	10.29"	6.79"	4.68"




**LUTRON HI-LUME PREMIER 0.1% DIMMABLE ELECTRONIC**



Soft-on, Fade-to-Black, continuous flicker-free dimming from 100% to 0.1.

PART NUMBER	CAPACITY	INPUT	OUTPUT	CLASS	LOCATION	L	W	H
L3D0-96W24V-U	96W	120-277V	24V	CLASS 2	IP20 DRY	10.5"	5.5"	2.0"



\*Performance can be affected by driver loading and dimmer type.