



# COLOR CHANGING RGBW LED NEON - 24V


Square XL Profile / Side Bending / Silicone



## TECHNICAL INFORMATION

NOTE: All data has +/- 5% tolerance.

WATTAGE	4.6W per foot
IP RATING	IP68 - wet locations. Protected against temporary submersion, limited protection against harsh environments.
PROFILE	Square
BEND ORIENTATION	Side Bending
HOUSING MATERIAL	Silicone, UV resistant per ISO 4892-3
OUTPUT	Red (618-624nm) - 23 lm/ft Green (522-528nm) - 63 lm/ft Blue (468-474nm) - 12 lm/ft 2700K - 55 lm/ft 3000K - 55 lm/ft 4000K - 55 lm/ft
INPUT VOLTAGE	24VDC
SEGMENT LENGTH	Every 6.6", not field-cuttable
MAXIMUM RUN	16 feet
DIMENSIONS	0.87" W x 0.87" H
MINIMUM BEND	15.75" diameter
INSTALLATION TEMP.	-40°F to 140°F
OPERATING TEMP.	-40°F to 140°F
WARRANTY	3 year limited
CONTROLS	Receiver/decoder and controller required.
POWER SUPPLY	Compatible with all non-dimmable 24VDC power supplies - see power supply section of website.



### ANTI-WICKING FERRULE


Standard on all LED Neon power cables.  
Located 4.5" from the connector.  
Protects against water ingress and circuit board corrosion.  
H 0.47" x W 1.18"

## MOUNTING OPTIONS (SOLD SEPARATELY)

See page 5 for more detail.

### Silicone Grip Mounting Clip

Part Number: LLI-NSX-MCL-SG-0.8IN  
0.80" L x 1.05" H x 1.05" W  
Recommended: 2 mounting clips for every 12in of Neon.



### Silicone Grip Mounting Channel

Part Number: LLI-NSX-EXT-SG-20IN/39IN  
20" L/39" L x 1.05" H x 1.05" W

**NOTE:** Neon sections may be mounted end-to-end on the non-power feed end to create the appearance of longer runs. End-to-end Neon sections must have a 0.5" to 1" gap to allow for expansion/contraction. A dark spot may be visible at <20ft viewing distance.

## PART NUMBER BUILDER / ORDERING GUIDE

Example part number: LLI-N4.6W-68-SXSS-R27-24V-96in

SERIES	IP RATING	TYPE	COLOR	VOLTAGE	LENGTH
LLI-N4.6W	68	SXSS		24V	
			R27		
			R30		
			R40		


Enter length in inches, up to 192"

# COLOR CHANGING RGBW LED NEON - 24V

Square XL Profile / Side Bending / Silicone


## ORIENTATION & MINIMUM BEND DIAMETER

---



## POWER FEED ORIENTATION GUIDE


---



# COLOR CHANGING RGBW LED NEON - 24V



Square XL Profile / Side Bending / Silicone

## POWER FEED & TERMINATION OPTIONS (IP68)






End Power Feed

SERIES	LENGTH
LLI-NSX-68-PWR5-EF	39IN 118IN 196IN 393IN




Rear Power Feed

SERIES	LENGTH
LLI-NSX-68-PWR5-RF	39IN 118IN 196IN 393IN




Side Right Power Feed

SERIES	SIDE	LENGTH
LLI-NSX-68-PWR5	SR	39IN 118IN 196IN 393IN



Side Left Power Feed


SERIES	SIDE	LENGTH
LLI-NSX-68-PWR5	SL	39IN 118IN 196IN 393IN



# COLOR CHANGING RGBW LED NEON - 24V

Square XL Profile / Side Bending / Silicone


## POWER FEED & TERMINATION OPTIONS (IP68)



End Cap

SERIES

LLI-NSX-68-EC




Jumper Power Connector (maximum 4 per run)

SERIES

LLI-NSX-68-CON5

SIDE LENGTH (L)

SR	12IN
SL	39IN
EF	118IN
RF	196IN
	393IN



# COLOR CHANGING RGBW LED NEON - 24V

Square XL Profile / Side Bending / Silicone

## OVERALL LENGTH / SEGMENT POINT GUIDE

Dimension tolerance of  $\pm 1/8"$ . Measurements listed below apply to Side Feed and Rear Feed Neon only. Add 1" to measurements below for End Feed Neon. Measurements below do not include area required for routing power wire. Add 1" distance to layout to account for routing end feed power wire. This product expands and contracts in varying ambient temperatures. If butting Neon end-to-end, add 1/2" to 1" gap between sections for expansion.


13.4"	20.0"	26.5"	33.1"	39.7"	46.2"	52.8"	59.3"	65.9"	72.5"	79.0"	85.6"
92.2"	98.7"	105.3"	111.8"	118.4"	125.0"	131.5"	138.1"	144.7"	151.2"	157.8"	164.4"
170.9"	177.5"	184.0"	190.6"	197.2"							

## MOUNTING CHANNEL

**NOTE:** Leave a 0.5" to 1" gap between Neon power feed and mounting channel, to avoid undue stress on power feed cables.

### SILICONE GRIP ALUMINUM MOUNTING CHANNEL

Recommended for ceiling and wall applications  
Silver anodized finish



#### Mounting Clip

Recommended 2 clips every 12"


Part Number: LLI-NSX-MCL-SG-0.8IN  
Dimensions: 0.8" L x 1.05" H x 1.05" W

#### 20" Mounting Channel

Part Number: LLI-NSX-EXT-SG-20IN  
Dimensions: 20" L x 1.05" H x 1.05" W

#### 39" Mounting Channel

Part Number: LLI-NSX-EXT-SG-39IN  
Dimensions: 39" L x 1.05" H x 1.05" W



### RECESSED SILICONE GRIP ALUMINUM MOUNTING CHANNEL

Recommended for ceiling and wall applications  
Silver anodized finish



#### Mounting Clip

Recommended 2 clips every 12"


Part Number: LLI-NSX-MCL-RSG-0.8IN  
Dimensions: 0.8" L x 1.04" H x 1.43" W

#### 20" Mounting Channel

Part Number: LLI-NSX-EXT-RSG-20IN  
Dimensions: 20" L x 1.04" H x 1.43" W


#### 39" Mounting Channel

Part Number: LLI-NSX-EXT-RSG-39IN  
Dimensions: 39" L x 1.04" H x 1.43" W



### FLEXIBLE ALUMINUM SILICONE GRIP MOUNTING CHANNEL

Side bend only




#### 20" Mounting Channel

Part Number: LLI-NSX-EXT-FSG-SB-20IN  
Dimensions: 20" L x 1.04" H x 1.05" W

#### 39" Mounting Channel

Part Number: LLI-NSX-EXT-FSG-SB-39IN  
Dimensions: 39" L x 1.04" H x 1.05" W



Minimum Bend Diameter  
toothed side inwards: 16.9"  
toothed side outwards: 15.7"


# COLOR CHANGING RGBW LED NEON - 24V

Square XL Profile / Side Bending / Silicone

POWER SUPPLY (SOLD SEPARATELY)

NON-DIMMABLE ELECTRONIC 



PART NUMBER	CAPACITY	INPUT	OUTPUT	CLASS	LOCATION	L	W	H
LLI-PS-NDE-030W-24V-KO	30W	100-277V	24V	CLASS 2	IP66 WET	6.5"	3.5"	1.02"
LLI-PS-NDE-060W-24V-KO	60W	100-277V	24V	CLASS 2	IP66 WET	7.4"	3.5"	1.2"
LLI-PS-NDE-096W-24V-KO	96W	100-277V	24V	CLASS 2	IP66 WET	8.7"	3.7"	1.7"
LLI-PS-NDE-200W-24V-KO	200W	100-277V	24V	CLASS 1	IP66 WET	10.3"	4.1"	1.8"
LLI-PS-NDE-300W-24V-KO	300W	100-277V	24V	CLASS 1	IP66 WET	10.9"	4.3"	1.8"



RF RECEIVER (SOLD SEPARATELY)

LLI-C-RCV-UR-RF-4CH

CONTROLLER COMPATIBILITY	Compatible with all RF LLI-C-CTRL controllers.
LED COMPATIBILITY	Static Color, Tunable White & RGB(W) LEDs
CHANNELS	4 Channel, 8 Amp
INPUT VOLTAGE	12V / 24V (power supply not included)
CAPACTIY	12V - 96W, 24V - 192W
FEATURES	Can be controlled by up to (8) controllers Can be synchronized with unlimited receivers up to 320ft away



# COLOR CHANGING RGBW LED NEON - 24V


Square XL Profile / Side Bending / Silicone

RF CONTROLLERS (SOLD SEPARATELY)

## REMOTE CONTROLLER

LLI-C-CTRL-RGBW-HH


RECEIVER COMPATIBILITY	Compatible with Universal RF receivers
LED COMPATIBILITY	RGB(W) LEDs
INPUT VOLTAGE	Battery operated (3 AAA batteries not included)
FEATURES	Programmable up to 4 zones, 3 scenes Color adjustment Light intensity adjustment



## TOUCH PANEL WALL CONTROLLER

LLI-C-CTRL-RGBW-TP-WH

RECEIVER COMPATIBILITY	Compatible with Universal RF receivers
LED COMPATIBILITY	RGB(W) LEDs
INPUT VOLTAGE	12V DC power supply required (not included)
FEATURES	Control range ≥ 65ft Programmable up to 3 scenes 4 color presets Color adjustment Light intensity adjustment



# COLOR CHANGING RGBW LED NEON - 24V


Square XL Profile / Side Bending / Silicone

## DMX DECODERS (SOLD SEPARATELY)

### DMX512 DECODER

#### LLI-C-DEC-DMX512-8A

LOCATION RATING	Indoor only
FUNCTION	Single color, variable white, RGB(W) LEDs
CHANNELS	4 channel output, 8 Amp maximum 512 addressable DMX channels
CAPACITY	12V - 96W maximum 24V - 192W maximum
COMPATIBILITY	Compatible with LLI-C-CTRL-DMX controllers




#### POWER

Power supply not included. 12V/24V non-dimming power supply required.

### RDM DMX512 DECODER

#### LLI-C-DEC-DMX512-8A-RDM

OUTPUT	8A maximum, 4 channels
LOCATION RATING	Indoor only
FUNCTION	RDM communication and PWM dimming for static white, single color, dynamic white, and RGB(W) LEDs
CHANNELS	4 channel output, 8 Amp maximum 512 addressable DMX channels
CAPACITY	12V - 96W maximum 24V - 192W maximum
COMPATIBILITY	Compatible with LLI-C-CTRL-DMX controllers



#### FEATURES

Can be controlled by up to eight (8) controllers. Can be synchronized with twenty (20) receivers.

#### POWER

Power supply not included. 12V/24V non-dimming power supply required.



# COLOR CHANGING RGBW LED NEON - 24V


Square XL Profile / Side Bending / Silicone

DMX WALL CONTROLLERS (SOLD SEPARATELY)

## STAND ALONE DMX WALL CONTROLLER, GU2

### LLI-C-CTRL-DMX-STICK-GU2

INCLUDED IN PACKAGE	Controller, CD-ROM, USB cable, connector block, power supply
OS/COMPUTER REQUIREMENTS	Mac OSx 10.6 or higher / Windows XP or higher, USB 2.0 port
PROGRAM SOFTWARE	Easy Stand Alone, ESA2 (included)
CONNECTIONS	Power (2 pins), DMX (3 pins), Port (2 pins), Micro-USB Port
MOUNTING	Single or double gang wall box
IP RATING	IP20 - dry locations only





### FEATURES

- Up to 24 dynamic or static scenes
- Wall mounted control panel with glass face, touch-sensitive buttons
- Programmable with included USB cable and software – no Ethernet or WiFi required

## STAND ALONE DMX WALL CONTROLLER, DE3

### LLI-C-CTRL-DMX-STICK-DE3

INCLUDED IN PACKAGE	Controller, connector block, power supply
OS/COMPUTER REQUIREMENTS	Mac OSx 10.6 or higher / Windows XP or higher / iOS phone or tablet / Android phone or tablet
PROGRAM SOFTWARE	Easy Stand Alone, ESA2 (Mac/Windows) DMX Lightpad 3 App (iOS/Android) Easy Remote App (iOS/Android)
CONNECTIONS	Power/DMX - screw terminal and RJ45 compatible Memory - MicroSD slot Programming - MicroUSB port
POWER SUPPLY	6VDC power supply (included)
MEMORY	MicroSD card (not included)
MOUNTING	Single or double gang wall box
IP RATING	IP20 - dry locations only



### FEATURES

- Multi-zone microSD memory
- Multi-room control with 500 scenes, 10 zones
- Integrated clock and calendar for scheduling events
- Touch-sensitive buttons
- USB and Ethernet connectivity for programming
- Windows/Mac software for programming dynamic effects
- iPhone/iPad/Android apps for remote control and program

# COLOR CHANGING RGBW LED NEON - 24V

Square Profile / Side Bending / Silicone

## DMX WALL CONTROLLERS (SOLD SEPARATELY)

### STAND ALONE DMX WALL CONTROLLER, CW4


LLI-C-CTRL-DMX-STICK-CW4	-	FINISH
		<input type="checkbox"/> BL Black glass
		<input type="checkbox"/> WH White glass

INCLUDED IN PACKAGE	Controller, connector block, power supply, mini-USB cable, ESA2 software, ESA Pro2 Software
OS/COMPUTER REQUIREMENTS	Mac OSx 10.6 or higher / Windows XP or higher
PROGRAM SOFTWARE	Easy Stand Alone, ESA2 (Mac/Windows)
CONNECTIONS	Power/DMX - screw terminal and RJ45 Programming - miniUSB port
POWER SUPPLY	Requires 5-10VDC 0.6A power supply (included)
MEMORY	Integrated flash memory
MOUNTING	Single or double gang wall box
IP RATING	IP20 - dry locations only



#### FEATURES



- Can be controlled directly from a computer, smartphone, or tablet
- Touch-sensitive buttons, glass face
- Up to 36 dynamic or static scenes
- 8 port triggers
- 1024 DMX channels control up to 340 RGB fixtures
- Windows/Mac software for programming dynamic effects
- Internal clock and calendar with sunrise/sunset triggering



### TOUCH PANEL DMX WALL CONTROLLER

#### LLI-C-CTRL-DMX-RGBW-TP

LED TAPE COMPATIBILITY	Compatible with 12-24V DC LED tapes
PROTOCOL	DMX512
ZONES	3 zones
INTERFACE	Glass touch control
WARRANTY	5 year limited



#### POWER

Power supply for controller not included.  
12V DC power supply required.