



plug & play

Outdoor Wall Washer/Grazer

3 YEAR
LIMITED
WARRANTY



IP66

FEATURES

- Highlight exterior or interior architectural features including surface textures, coves, and facade details.
- Different beam angles to graze or wash a surface.
- Interconnect up to (3) 50W units or (6) 25W units.
- Plug and play connectors, makes it easy to interconnect.
- Adjustable mounting brackets rotate up to 180°.

Reference website for additional information

SPECIFICATIONS

PART NUMBER	LLI-OWG-XX	
MODELS	20.0"	39.0"
WATTAGE	25 W	50 W
CCT	27K, 30K, 35K, 42K, 52K	
OUTPUT	2250 - 2500 lm/ft	4500 - 5000 lm/ft
BEAM ANGLE	15°, 25°, 30°, 40°, 60°, 10x30°, 10x45°, 10x70°, 20x60°	
IP RATING	IP66 - wet locations. not suitable for submersion, limited protection against harsh environments	
FINISH	Black powder coat	
MAX RUN	Max run (3) 50W units, (6) 25W units or max 8A of combined lengths	
INPUT VOLTAGE	24VDC, requires a remote 24V power supply	
MOUNTING	Adjustable locking bracket	

GENERAL WIRING DIAGRAM

